

## ACCESSORIES FOR POWER TOOLS

### HSS-CO JOBBER DRILL



#### PRODUCT FEATURES

135° point angle with chamfering adjustment - enables quick drilling, while saving time during marking out. Made from the highest class HSS steel with 5% cobalt. High resistance to temperature. For drilling in high alloy, titanium, acid-resistant, stainless, and creep-resisting steels and cast iron (durability above 900 N/m<sup>2</sup>) and other difficult to process materials. Drills made entirely by grinding - they guarantee high accuracy and rectilinearity of holes. Packed and sold in a plastic rectangular tube: dimensions 0.5 - 8.0 mm of 10 pcs; dimensions: 8.1 - 13.0 mm of 5 pcs; dimensions 14 - 20.0 mm of 1 pcs.

CODE	Ø [MM]	WORKING PART LENGHT [MM]	TOTAL LENGHT [MM]	
78008	0,8	10	30	10/200/1000
78010	1	12	34	10/200/1000
78015	1,5	18	40	10/200/1000
78020	2	24	49	10/200/1000
78025	2,5	30	57	10/200/1000
78030	3	33	61	10/200/1000
78032	3,2	36	65	10/200/1000
78035	3,5	39	70	10/200/1000
78038	3,8	43	75	10/250/500
78040	4	43	75	10/250/1500
78042	4,2	43	75	10/250/1500
78045	4,5	47	80	10/250/1500
78048	4,8	52	86	10/250/500
78050	5	52	86	10/250/1500
78051	5,1	52	86	10/250/500
78052	5,2	52	86	10/250/500
78055	5,5	57	93	10/250/1500
78060	6	57	93	10/250/1500
78061	6,1	63	101	10/100/300
78062	6,2	63	101	10/100/300

**PROLINE®**

<https://pl-pl.facebook.com/ProlineTools>  
[www.proline-tools.com](http://www.proline-tools.com)

HSS-CO JOBBER DRILL



PRODUCT FEATURES

135° point angle with chamfering adjustment - enables quick drilling, while saving time during marking out. Made from the highest class HSS steel with 5% cobalt. High resistance to temperature. For drilling in high alloy, titanium, acid-resistant, stainless, and creep-resisting steels and cast iron (durability above 900 N/m<sup>2</sup>) and other difficult to process materials. Drills made entirely by grinding - they guarantee high accuracy and rectilinearity of holes. Packed and sold in a plastic rectangular tube: dimensions 0.5 - 8.0 mm of 10 pcs; dimensions: 8.1 - 13.0 mm of 5 pcs; dimensions 14 - 20.0 mm of 1 pcs.

CODE	Ø [MM]	WORKING PART LENGHT [MM]	TOTAL LENGHT [MM]	
78065	6,5	63	101	10/100/600
78070	7	69	109	10/100/600
78075	7,5	69	109	10/100/400
78080	8	75	117	10/100/400
78081	8,1	75	117	5/50/200
78082	8,2	75	117	5/50/200
78085	8,5	75	117	5/50/200
78090	9	81	125	5/50/200
78095	9,5	81	125	5/50/200
78100	10	87	133	5/50/200
78102	10,2	87	133	5/50/200
78105	10,5	87	133	5/50/200
78110	11	94	142	5/50/200
78115	11,5	94	142	5/50/200
78120	12	101	151	5/50/200
78125	12,5	101	151	5/50/200
78130	13	101	151	5/50/200
78140	14	108	160	100
78150	15	114	169	50
78160	16	120	178	50
78180	18	130	191	50
78200	20	140	205	50