



HSS TWIST DRILL BLISTER



PRODUCT FEATURES


135° point angle with chamfering adjustment - enables quick drilling, while saving time during centre punching. Ground edges. Material - refined HSS. Packed and sold in a blister pack: dimensions: 0.8 – 2.0 mm of 5 pcs; dimensions: 2.5 – 3.5 mm of 3 pcs; dimensions: 4.0 – 5.0 mm of 2 pcs; dimensions: 5.1 – 13.0 mm of 1 pcs.



CODE	Ø [MM]	WORKING PART LENGHT [MM]	TOTAL LENGHT [MM]	QUANTITY [PCS]		
79008K	0,8	10	30	5	x	20/200
79010K	1	12	34	5	x	20/200
79015K	1,5	20	43	5	x	20/200
79020K	2	24	49	5	x	20/200
79025K	2,5	30	57	3	x	20/200
79030K	3	33	61	3	x	20/200
79032K	3	36	65	3	x	20/200
79035K	3,5	39	70	3	x	20/200
79040K	4	43	75	2	x	20/200
79041K	4,1	43	75	2	x	20/200
79042K	4,2	43	75	2	x	20/200
79045K	4,5	47	80	2	x	20/200
79048K	4,8	52	86	2	x	20/200
79050K	5	52	86	2	x	20/200
79051K	5,1	52	86	1	x	20/200
79052K	5,2	52	86	1	x	20/200
79055K	5,5	57	93	1	x	20/200
79060K	6	57	93	1	x	20/200



HSS TWIST DRILL BLISTER



PRODUCT FEATURES

135° point angle with chamfering adjustment - enables quick drilling, while saving time during centre punching. Ground edges. Material - refined HSS. Packed and sold in a blister pack: dimensions: 0.8 – 2.0 mm of 5 pcs; dimensions: 2.5 – 3.5 mm of 3 pcs; dimensions: 4.0 – 5.0 mm of 2 pcs; dimensions: 5.1 – 13.0 mm of 1 pcs.



CODE	Ø [MM]	WORKING PART LENGHT [MM]	TOTAL LENGHT [MM]	QUANTITY [PCS]		
79065K	6,5	63	101	1	x	20/200
79070K	7	69	109	1	x	20/200
79075K	7,5	69	109	1	x	20/200
79080K	8	75	117	1	x	20/200
79085K	8,5	75	117	1	x	20/200
79090K	9	81	125	1	x	20/200
79095K	9,5	81	125	1	x	20/200
79100K	10	87	133	1	x	20/200
79105K	10,5	87	133	1	x	20/200
79110K	11	94	142	1	x	20/200
79115K	11,5	94	142	1	x	20/200
79120K	12	101	151	1	x	20/200
79125K	12,5	101	151	1	x	20/120
79130K	13	101	151	1	x	20/120